

TECHNICAL SPECIFICATIONS
SEAT Mii by MANGO 5D



	1.0 60 HP	1.0 60 HP ECOMOTIVE	1.0 75 HP	1.0 75 HP ECOMOTIVE
ENGINE				
Cylinder/Valve (Total)	3 Cyl. - 4 v			
Displacement (cc)	999			
Bore and stroke (mm)	74,5 x 76,4			
Compression ratio	10,5			
Maximum power (Kw/hp/rpm)	44/60/5000-6000		55/75/6200	
Max. Torque (NM/rpm)	95 / 3000-4300			
Fuel supply system	MPI			
Ignition	Positiv Ignition (Electronic map-controlled ignition)			
Fuel type	ROZ 95			
Emissions standard	EU5 J			
Alternator (A)	90A / 110A	110A	90A / 110A	110A
Battery (Ah)	36Ah / 44Ah	59Ah	36Ah / 44Ah	59Ah
PERFORMANCE				
Max. Speed (Km/h)	160	161	171	172
Acceleration 0-100 km/h (s)	14,4		13,2	
MASS EMISSION				
CO2 Combined (g/Km)	105	95	108	98
FUEL CONSUMPTION				
Combined (l/100 Km)	4,5	4,1	4,7	4,2
TRANSMISSION				
Gearbox type:	MQ100-5F			
I	3,643			
II	1,955			
III	1,270			
IV	0,959			
V	0,796			
VI				
R	3,615			
Group ratio	3,894		4,166	
Speed 1000 rpm in IV/V/VI (km/h)	28,7 / 34,6		26,9 / 32,4	
CHASIS				
Front suspension	Independent type McPherson - coil springs - hydraulic dampers - Stabilizing bar Ø 18 mm			
Rear suspension	Semirigid rear axle - coil springs - hydraulic dampers			
Steering system	Mechanical Steering or C-EPS (Column Electric Power Steering)			
Turning diameter (m)	Mechanical (10,9) C-EPS (9,8)			
Brake system	ABS Standart, Option ESP			
Front / Rear brake type	Ventilated front brakes / Drum brakes in rear axle			
Front brakes (mm)	256x22			
Rear brakes (mm)	200x40			
Rims (")	5.0J x 14" / 6.0J x 15"			
Tyres	165/70 R14 - 175/65 R14 - 185/55 R15			
PACKAGE				
Body type	5 doors			
Length / width / height (mm)	3557 / 1641 / 1478			
Wheelbase (mm)	2420			
Front/Rear track (mm)	1428 / 1424			
Boot capacity (L)	251			
Petrol tank capacity (L)	35			
WEIGHTS				
In running order with driver (Kg)	929	940	929	940
Max. Weight allowed (Kg)	1290			