## Volvo C40 Recharge

| PROPULSION  | Twin  |  |
|---|---|--|
| Туре  | Electric motor front / rear   |  |
| Electrical motor max output, kW (kW/engine) (hp)/rpm (metric)                               | 300 (150 × 2) (408) / 13 900  |  |
| Electrical motor max output, kW (kW/engine) (hp)/rpm (mechanical)                           | 300 (150 x 2) (402) / 13 900  |  |
| Max torque, Nm (Nm/engine)/rpm  | 660 (330×2) / up to 4350  |  |
|   |   |  |
| PERFORMANCE   |   |  |
| Acceleration, 0–100 km/h (sec)  | 4.9   |  |
| Acceleration, 0–60 mph (sec)  | 4.7   |  |
| Top speed, km/h   |   |  |
| Top speed, mph  |   |  |
| BATTERY   |   |  |
| Battery content, total amount of energy, (kWh) (Nominal)                                    | 78  |  |
| Battery content, total amount of energy, (kWh) (Usable)                                     | 75  |  |
| CHARGING  |   |  |
| AC, h (11 kW) (h)   | 8   |  |
| DC, min (150 KW) ** (min)   | 40  |  |
| **(0-80% loading rate, battery temp 20-35 deg C)  |   |  |
| RANGE   |   |  |
| Electric Range, (WLTP) (Km) (EU)  | Estimated WLTP range of 420 km  |  |
| Electric Range, (EPA) (Miles) (US)  | Estimated WEIT range of 420 kin   |  |
| Length, (cm) Width, (incl. mirrors) (cm)  | 443.1   |  |
| Wildin, (incl. mirrors) (cm) Height, (incl. shark fin) (cm)                                 | 203.5   |  |
| Track, front (cm)   | 158.2<br>159.8  |  |
| Track, rear (cm) (Rim size: 19" / 20")  |   |  |
| Hack, Teal (cit) (killi size: 19-7-20-)   | 162.3   |  |
| INTERIOR MEASUREMENTS   |   |  |
| Headroom with panorama roof (front/rear) (H61-1 SR/H61-2 SR) (cm)                           | 100.2 / 93.2  |  |
| Passenger compartment width at shoulder height (front/rear) (w3-1/w3-2) (cm)                | 144.0 / 142.9   |  |
| Leg room (front/rear) (L34/L51-2) (cm)  | 104.0 / 91.7  |  |
| Cargo volume, including under floor storage (v211-2) (litres)                               | 413   |  |
| Cargo volume, including under floor storage (v214-2) (litres)                               | 413   |  |
| Frunk volume, with Tool kit (litres) (EU + RoW)   | 31  |  |
| Frunk volume, with Tool kit (litres) (US)   | 21  |  |
|   |   |  |
| WEIGHTS/MISCELLANEOUS   | 2405  |  |
| Weight, kg (depending on setup)   | ~ 2185  |  |
| Max trailer weight, kg  | 1800  |  |
| Max roof load, kg   |   |  |
| CHASSIS   |   |  |
| Suspension front MacPherson Suspension, Coil Spring   | MacPherson Suspension, Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar                              |  |
| rear Rear multi-link Suspension with Coil   | Rear multi-link Suspension with Coil Springs, Hydraulic Shock Absorbers, Stabilizer Bar                     |  |
| Steering Electrical Power Assisted Rack Braking system Antilock Braking System (ABS) with I | Electrical Power Assisted Rack  |  |
|   | Antilock Braking System (ABS) with Electronic Brake Distribution (EBD) and Electronic Brake Assistance (EBA |  |



